



PART NO./DWG. NO.	DESCRIPTION	MATERIAL	QTY.
1	TOP	CAST IRON	1
2	FLANGE	CAST IRON	1
3	BOLT	CAST IRON	1
4	GASKET	ARMSTRONG	1
5	SEAL	BUNA-N-RUBBER	1
6S	FLOAT	STAINLESS STEEL	1
11	BOLT	STEEL	6
12	NUT	STEEL	6
29	PLUG	BRASS	1
29A	PLUG-5	BRASS	1

- NOTES:**
1. INLET SIZE: 2" NPT; OUTLET SIZE: 2" NPT.
  2. APPROXIMATE WEIGHT - 44 lbs.
  3. WHEN OPERATING PRESSURE IS BELOW 20 psig, REPLACE ITEM NO. 5 WITH SOFT SEATING MATERIAL, DWG. NO. 3-5L.
  4. WHEN OPERATING PRESSURE IS ABOVE 150 psig, REPLACE ITEM NO. 5 WITH HARD SEATING MATERIAL, DWG. NO. 3-5H.

<p>DO NOT SCALE DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED (REFER TO DIMENSIONS &amp; TOLERANCES &amp; FINISH)</p>		<p>2" AIR AND VACUUM VALVE</p>	
DESIGNED BY	DATE	DWG. NO.	REV.
BUL	12-22-10	AL20	0
CHECKED BY	DATE	SHEET	OF
DJF	12-22-10	1	1

**Crispin Air Valves**