



PART NO./DWG. NO.	DESCRIPTION	MATERIAL	QTY.
1	3-1S TOP FLANGE	CAST IRON	1
2	3-2C FLANGE BODY	CAST IRON	1
3	3-3C GASKET	ARMSTRONG	1
4	3-4 SEAT	BUNA-N-RUBBER	1
5	3-5 SEAT	STAINLESS STEEL	1
6S	3-6S FLOAT	STEEL	6
11	3-11 BOLT	STEEL	6
12	3-12 NUT	STEEL	6
15	NPL 2X3.5 NIPPLE	STEEL	1
16	202-9 COMPANION FLANGE	CAST IRON	1
29	27-29 PLUG	BRASS	1
29A	PLG-5 PLUG	BRASS	1

INLET FLANGE DATA	
FLANGE DIAMETER	6.00 in.
FLANGE THICKNESS	0.62 in.
BOLT CIRCLE DIAMETER	4.75 in.
NUMBER OF BOLT HOLES	4
BOLT HOLE DIAMETER	0.75 in.

- NOTES:**
1. INLET SIZE: 2" CLASS 125 FLANGED
  2. WEIGHT: 46 lbs.
  3. WHEN OPERATING PRESSURE IS BELOW 20 psig, REPLACE ITEM NO. 5 WITH SOFT SEATING MATERIAL, DWG. NO. 3-5L.
  4. WHEN OPERATING PRESSURE IS ABOVE 150 psig, REPLACE ITEM NO. 5 WITH HARD SEATING MATERIAL, DWG. NO. 3-5H.

DO NOT SCALE DIMENSIONS UNLESS OTHERWISE SPECIFIED  
 UNLESS OTHERWISE SPECIFIED  
 UNLESS OTHERWISE SPECIFIED

**Crispin Air Valves**  
 2" CLASS 125,  
 AIR/VACUUM VALVE

REV	DESCRIPTION	DATE	APPROVED	CHECKED	DATE	DWG. NO.	SHEET	OF
0				DJF	9-10-10	AL21	1	1