



PARTS LIST			
PART NO./DWG. NO.	DESCRIPTION	MATERIAL	QTY.
1	3-1S TOP FLANGE	CAST IRON	1
2	3-2C FLANGE	CAST IRON	1
3	3-3C BODY	CAST IRON	1
4	3-4 GASKET	ARMSTRONG	1
5	3-5 SEAL	BUINA-N-RUBBER	1
6S	3-6S FLOAT	STAINLESS STEEL	1
11	3-11 BOLT	STEEL	6
12	3-12 NUT	STEEL	6
15	NPL 2X3.5 NIPPLE	STEEL	1
16	202-9H COMPANION FLANGE	CAST IRON	1
29	27-29 PLUG	BRASS	1
29A	PLG-5 PLUG	BRASS	1

INLET FLANGE DATA	
FLANGE DIAMETER	6.50 in.
FLANGE THICKNESS	0.88 in.
BOLT CIRCLE DIAMETER	5.00 in.
NUMBER OF BOLT HOLES	8
BOLT HOLE DIAMETER	0.75 in.

- NOTES:**
1. INLET SIZE: 2" CLASS 250 FLANGED
 2. WEIGHT: 49 lbs.
 3. WHEN OPERATING PRESSURE IS BELOW 20 psig, REPLACE ITEM NO. 5 WITH SOFT SEATING MATERIAL, DWG. NO. 3-5L.
 4. WHEN OPERATING PRESSURE IS ABOVE 150 psig, REPLACE ITEM NO. 5 WITH HARD SEATING MATERIAL, DWG. NO. 3-5H.

Crispin Air Valves
2" CLASS 250, AIR/VACUUM VALVE

REV	DESCRIPTION	DATE	APPROVED

ORDERED BY	DATE	SIZE	DWG. NO.
DJF	7-12-14	C	AL22
DRAWN	SCALE 1:50 = 1:50	SHEET	1 OF 1

DO NOT SCALE DIMENSIONS UNLESS OTHERWISE SPECIFIED
UNLESS OTHERWISE SPECIFIED
UNLESS OTHERWISE SPECIFIED