



PARTS LIST				
ITEM NO.	PART NUMBER	DESCRIPTION	MATERIAL	QTY.
1	4-1S	TOP	DUCTILE IRON	1
2	4-2C	COVER FLANGE	DUCTILE IRON	1
3	4-3C	BODY	DUCTILE IRON	1
4	4-4	COVER GASKET	ARMSTRONG	1
5	4-5	SEAT	BUNA-N RUBBER	1
6	4-6S	FLOAT	STAINLESS STEEL	1
7	HHCS.625X2.5	COVER BOLT	STEEL	6
8	FHN.625-11	COVER NUT	STEEL	6
9	PLG.25	FLANGE PLUG	BRASS	1
10	PLG.5	BODY PLUG	BRASS	1

- NOTES:**
1. INLET SIZE: 3" NPT  
OUTLET SIZE: 3" NPT
  2. APPROXIMATE WEIGHT: 83 lbs
  3. VALVE WILL BE COATED EXTERNALLY WITH PHENOLIC ALKYD PRIMER

REV.	DESCRIPTION	DATE	APPROVED
1	REDRAWN IN SOLIDWORKS		

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
1	REDRAWN IN SOLIDWORKS		

**CRISPIN VALVES**

TITLE:  
**3" AIR / VACUUM RELEASE VALVE**

SIZE	DWG. NO.	REV
<b>B</b>	<b>AL30 8205976</b>	<b>1</b>

SCALE: 0.63:1 WT: LB SHEET 1 OF 1

UNLESS OTHERWISE SPECIFIED:		NAME	DATE
DIMENSIONS ARE IN INCHES		DRAWN	DJF 10-17-19
XX DIMENSIONS	+ .1	CHECKED	- -
XXX DIMENSIONS	+ .01	ENG APPR.	- -
XXXX DIMENSIONS	+ .005	MFG APPR.	- -
DRILLED HOLES	+ .01	Q.A.	- -
ANGLES	+ .1	FILE LOCATION:	\\S2\sl1\drawings\ASSEMBLY\AVV\
CONCENTRIC DIAMETERS	SEE BELOW	FILE NAME:	AL30 8205976 r1
MACHINED	005 TIR		
MACHINED TO CAST	02 TIR		
MACHINED SURFACES	125 BMS		
REMOVE SPIRES			
BREAK SHARP EDGES			

**PROPRIETARY AND CONFIDENTIAL**  
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF CRISPIN VALVE. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF CRISPIN VALVE IS PROHIBITED.

DO NOT SCALE DRAWING