



PARTS LIST				
PART NO.	DWG. NO.	DESCRIPTION	MATERIAL	QTY.
1S	4-1S	TOP	CAST IRON	1
2	4-2C	FLANGE	CAST IRON	1
3	4-3CF	BODY	CAST IRON	1
4	4-4	GASKET	ARMSTRONG	1
5	4-5	SEAT	BUNA-N RUBBER	1
6	4-6S	FLOAT	STAINLESS STEEL	1
11	5-11	BOLT	STEEL	6
12	4-12	NUT	STEEL	6
29	27-29	PLUG	BRASS	1
29A	PLG-.5	PLUG	BRASS	1

INLET FLANGE DATA	
FLANGE DIAMETER	7.50 in.
FLANGE THICKNESS	0.75 in.
BOLT CIRCLE DIAMETER	6.00 in.
NUMBER OF BOLT HOLES	4
BOLT HOLE DIAMETER	0.75 in.

- NOTES:**
1. INLET SIZE: 3" CLASS 125 FLANGED
  2. WEIGHT: 89 lbs.
  3. WHEN OPERATING PRESSURE IS BELOW 20 psig, REPLACE ITEM NO. 5 WITH SOFT SEATING MATERIAL DWG. NO. 4-SL.
  4. WHEN OPERATING PRESSURE IS ABOVE 150 psig, REPLACE ITEM NO. 5 WITH HARD SEATING MATERIAL DWG. NO. 4-SH.

**Crispin Air Valves**

**3" CLASS 125 AIR/VACUUM VALVE**

DO NOT SCALE DRAWING DIMENSIONS ARE IN INCHES	DATE: 6-13-15	DWG. NO.: AL31	REV: 0
REVISIONS:	SIZE: C	SCALE: 0.75" = 1.00"	SHEET: 1 OF 1
REV: 0	DESCRIPTION: AIR/VACUUM VALVE	DATE: 6-13-15	APPROVED: [Signature]
REV: 0	DESCRIPTION: AIR/VACUUM VALVE	DATE: 6-13-15	APPROVED: [Signature]