



PARTS LIST				
PART NO.	DWG. NO.	DESCRIPTION	MATERIAL	QTY.
1S	4-1S	TOP	CAST IRON	1
2	4-2C	FLANGE	CAST IRON	1
3	4-3GFH	BODY	CAST IRON	1
4	4-4	GASKET	ARMSTRONG	1
5	4-5	SEAT	BUNA-N RUBBER	1
6	4-6S	FLOAT	STAINLESS STEEL	1
11	5-11	BOLT	STEEL	6
12	4-12	NUT	STEEL	6
29	27-29	PLUG	BRASS	1
29A	PLG-5	PLUG	BRASS	1

INLET FLANGE DATA	
FLANGE DIAMETER	8.25 in.
FLANGE THICKNESS	1.12 in.
BOLT CIRCLE DIAMETER	6.62 in.
NUMBER OF BOLT HOLES	8
BOLT HOLE DIAMETER	0.88 in.

- NOTES:**
1. INLET SIZE: 3" CLASS 250 FLANGE
  2. APPROXIMATE WEIGHT - 95 lbs.
  3. WHEN OPERATING PRESSURE IS BELOW 20 psig, REPLACE ITEM NO. 5 WITH SOFT SEATING MATERIAL DWG. NO. 4-SL.
  4. WHEN OPERATING PRESSURE IS ABOVE 150 psig, REPLACE ITEM NO. 5 WITH HARD SEATING MATERIAL DWG. NO. 4-SH.

**Crispin Air Valves**

**3" CLASS 250 AIR/VACUUM VALVE**

DO NOT SCALE DRAWING DIMENSIONS ARE IN INCHES		DATE: 06/29/86	REV: 0
DESIGNED BY: BUL	CHECKED BY: LAD	DATE: 06/29/86	REV: 0
DRAWN: LAD		SCALE: 0.75 = 1.00	SHEET: 1 OF 1