



PARTS LIST				
PART NO.	DWG. NO.	DESCRIPTION	MATERIAL	QTY.
1S	5-1S	TOP	CAST IRON	1
2	5-2C	FLANGE	CAST IRON	1
3	5-3C	BODY, SCREWED	CAST IRON	1
4	5-4	GASKET	ARMSTRONG	1
5	5-5	SEAT	BUNA-N RUBBER	1
6S	5-6S	FLOAT	STAINLESS STEEL	1
11	30-33	BOLT	STEEL	8
12	4-12	NUT	STEEL	6
29	27-29	PLUG	BRASS	1
29A	PLG-.5	PLUG	BRASS	1
55	EN 5/8" -11	EYE NUT	FORGED STEEL	2

- NOTES:**
1. INLET SIZE: 4" NPT; OUTLET SIZE: 4" NPT.
 2. APPROXIMATE WEIGHT - 154 lbs. REPLACE
 3. WHEN OPERATING PRESSURE IS BELOW 20 psig, REPLACE ITEM NO. 5 WITH SOFT SEATING MATERIAL DWG. NO. 5-5L.
 4. WHEN OPERATING PRESSURE IS ABOVE 150 psig, REPLACE ITEM NO. 5 WITH HARD SEATING MATERIAL DWG. NO. 5-5H.

DO NOT SCALE DIMENSIONS ARE IN INCHES		4" AIR/VACUUM VALVE	
REVISION:	DATE:	DWG. NO.:	SHEET 1 OF 1
CHECKED: BUL	DATE: 12-7-05	AL40	
DRAWN: DJF	SCALE: AS SHOWN		

Crispin Air Valves

4" AIR/VACUUM VALVE