



PARTS LIST				
PART NO.	DWG. NO.	DESCRIPTION	MATERIAL	QTY.
1S	5-1S	TOP	CAST IRON	1
2	5-2C	FLANGE	CAST IRON	1
3	5-3GFH	BODY	CAST IRON	1
4	5-4	GASKET	ARMSTRONG	1
5	5-5	SEAT	BUNA-N RUBBER	1
6S	5-6S	FLOAT	STAINLESS STEEL	1
11	30-33	BOLT	STEEL	8
12	4-12	NUT	STEEL	6
29	27-29	PLUG	BRASS	1
29A	PLG-.5	PLUG	BRASS	1
55	EN.625-11	EYE NUT	FORGED STEEL	2

INLET FLANGE DATA	
FLANGE DIAMETER	10.00 in.
FLANGE THICKNESS	1.25 in.
BOLT CIRCLE DIAMETER	7.88 in.
NUMBER OF BOLT HOLES	8
BOLT HOLE DIAMETER	0.88 in.

- NOTES:**
1. INLET SIZE: 4" CLASS 250 FLANGE
  2. OUTLET SIZE: 4" NPT
  3. APPROXIMATE WEIGHT: 181 lbs.
  4. WHEN OPERATING PRESSURE IS BELOW 20 psig, REPLACE ITEM NO. 5 WITH SOFT SEATING MATERIAL DWG. NO. 5-SL.
  5. WHEN OPERATING PRESSURE IS ABOVE 150 psig, REPLACE ITEM NO. 5 WITH HARD SEATING MATERIAL DWG. NO. 5-SH.

DO NOT SCALE DRAWING DIMENSIONS ARE IN INCHES		<b>Crispin Air Valves</b> 4" CLASS 250 AIR/VACUUM VALVE	
CHECKED BY: BULL	DATE: 5-11-11	DWG. NO. AL42	REV. 0
DRAWN BY: DJF	SCALE: 0.75 = 1.00	SHEET 1 OF 1	