



AIR / VACUUM PARTS LIST				
PART NO.	DWG. NO.	DESCRIPTION	MATERIAL	QTY.
1S	60-1S	TOP	CAST IRON	1
2	60-2H	FLANGE	CAST IRON	1
3F	60-3F	BODY	CAST IRON	1
4	60-4	GASKET	ARMSTRONG	1
5	60-5	SEAT	BUNA-N RUBBER	1
6S	60-6	FLOAT	STAINLESS STEEL	1
11	80-11	BOLT	STEEL	8
11A	606-11A	BOLT	STEEL	2
12	60-12	NUT	STEEL	10
13	60-13	BOLT	STEEL	10
29A	PLG.5	PLUG	BRASS	2
55	80-55	LIFTING LUG	STEEL	2

INLET FLANGE DATA	
FLANGE DIAMETER	11.00 in.
FLANGE THICKNESS	1.00 in.
BOLT CIRCLE DIAMETER	9.50 in.
NUMBER OF BOLT HOLES	8
BOLT HOLE DIAMETER	0.88 in.

- NOTES:**
1. INLET SIZE: 6" CLASS 125 FLANGE
 2. APPROXIMATE WEIGHT: 174 lbs.
 3. WHEN OPERATING PRESSURE IS BELOW 20 psig, REPLACE ITEM NO. 5 WITH SOFT SEATING MATERIAL DWG. NO. 60-5L.
 4. WHEN OPERATING PRESSURE IS ABOVE 150 psig, REPLACE ITEM NO. 5 WITH HARD SEATING MATERIAL DWG. NO. 60-5H.

Crispin Valves
 6" CLASS 125
 AIR / VACUUM VALVE

CHECKED BY: BUL	DATE: 12-2-11	SIZE: C	DWG. NO.: AL61	REV: 0
DESIGNED BY: DJF	DATE: 12-2-11	SCALE: 0.75 = 1.00	SHEET: 1	OF: 1

24 HOUR STATE SERVICE
 100 YEARS OF SERVICE
 UNITED STATES PATENTED
 FINISHED UNDER TOLERANCE 34.013
 UNLESS OTHERWISE SPECIFIED
 FINISHED UNDER TOLERANCE 34.013
 UNLESS OTHERWISE SPECIFIED
 FINISHED UNDER TOLERANCE 34.013
 UNLESS OTHERWISE SPECIFIED