



SECTION A-A

AIR / VACUUM RELEASE VALVE PARTS LIST				
ITEM	PART NUMBER	DESCRIPTION	MATERIAL	QTY
1	36-U6X-2	COVER	A351 GR. CF8M	1
2	28-3X-6FF	VALVE BODY	A351 GR. CF8M	1
3	AS568A-272	COVER O-RING	BUNA-N RUBBER	1
4	36-A6X-5	SEAT	BUNA-N RUBBER	1
5	36-A6X-3	SEAT RETAINER	316 STAINLESS STEEL	1
6	36-A6-6	VALVE ASSEMBLY	316 STAINLESS STEEL	1
7	36-A6X-7	FLOAT GUIDE PLATE	316 STAINLESS STEEL	1
8	36-A6-8	FLOAT ROD GUIDE	NYLATRON	1
9	36-A6-9	FLOAT	316 STAINLESS STEEL	1
10	36-A10-11	FLOAT ROD GUIDE NUT	316 STAINLESS STEEL	1
11	36-A6X-13	STAND OFF	316 STAINLESS STEEL	4
12	36-A3-19	SEAT RETAINER BOLT	316 STAINLESS STEEL	8
13	28-11X	CLAMP HALF	316 STAINLESS STEEL	2
14	3-11F	CLAMP BOLT	316 STAINLESS STEEL	2
15	LW-5	LOCKWASHER	316 STAINLESS STEEL	2
16	3-12	CLAMP NUT	316 STAINLESS STEEL	2
17	36-33	1" PLUG	316 STAINLESS STEEL	2

INLET FLANGE DATA	
FLANGE DIAMETER	11.00 in.
FLANGE THICKNESS	1.00 in.
BOLT CIRCLE DIAMETER	9.50 in.
NUMBER OF BOLT HOLES	8
BOLT HOLE DIAMETER	0.88 in.

- NOTES:
1. INLET SIZE: 6" CLASS 150
FLAT FACE FLANGE
OUTLET SIZE: 1" NPT
 2. WORKING PRESSURE: 20-200 PSIG
 3. APPROXIMATE WEIGHT: 136 lbs

UNLESS OTHERWISE SPECIFIED:		NAME	DATE	CRISPIN VALVES		
XXXX DIMENSIONS	AS SHOWN	DRAWN	DJF		1-16-17	
XXXX DIMENSIONS	AS SHOWN	CHECKED	-	TITLE: 6" CLASS 150 (X SERIES) AIR & VACUUM VALVE		
XXXX DIMENSIONS	AS SHOWN	ENG APPR	-			
XXXX DIMENSIONS	AS SHOWN	MFG APPR	-			
XXXX DIMENSIONS	AS SHOWN	QA	-			
FILE LOCATION:	Y:\ASSEMBLY\X Series\AA3\DRAWINGS\AA61			SIZE	DWG. NO.	REV
FILE LOCATION:	Y:\ASSEMBLY\X Series\AA3\DRAWINGS\AA61			C	AX61	0
SCALE: 1:3	WT: LB	SHEET 1 OF 1				

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
K-FLO by Crispin Valves. ANY
REPRODUCTION IN PART OR AS A
WHOLE WITHOUT THE WRITTEN
PERMISSION OF
K-FLO IS PROHIBITED.
"DO NOT SCALE DRAWINGS"