

DEEP WELL AIR RELEASE VALVE PARTS LIST								
PART NO.	DWG. NO.	DESCRIPTION	MATERIAL	QTY.				
1D	10-1D	DEEP WELL TOP	CAST IRON	1				
1DS	10-1DS	DEEP WELL STEM STEEL						
1DN	60-12	NUT	STEEL	1				
2	3-2C	FLANGE	CAST IRON	1				
3	3-3C	BODY	CAST IRON	1				
4	3-4	GASKET	ARMSTRONG	1				
5	3-5	SEAT	BUNA-N RUBBER	1				
6S	3-6S	FLOAT	STAINLESS STEEL	1				
11	3-11	BOLT	STEEL	6				
12	3-12	NUT	STEEL	6				
29A	PLG5	PLUG	BRASS	1				
29B	.25SOCHDNPTPL	PLUG	BRASS	1				
DEEP WELL AIR RELEASE VALVE PARTS LIST								
CP1	NPL 2X3	NIPPLE	STEEL	1				
CP2	202-9	COMP. FLANGE	CAST IRON	1				

INLET FLANGE DATA						
FLANGE DIAMETER	6.00 in.					
FLANGE THICKNESS	0.62 in.					
BOLT CIRCLE DIAMETER	4.75 in.					
NUMBER OF BOLT HOLES	4					
BOLT HOLE DIAMETER	0.75 in.					

- NOTES:

 1. INLET SIZE: 2" CLASS 125 FLANGED
 OUTLET SIZE: 2" NPT.

 2. APPROXIMATE WEIGHT 55 lbs.

 3. WHEN OPERATING PRESSURE IS BELOW 20 psig, REPLACE ITEM NO. 5 WITH SOFT SEATING MATERIAL DWG. NO. 3—5—L.

 4. WHEN OPERATING PRESSURE IS ABOVE 150 psig, REPLACE ITEM NO. 5 WITH HARD SEATING MATERIAL DWG. NO. 3—5—H.

	DO NOT SCALE DRAWING DIMENSIONS ARE IN INCHES			Cris	spi	n Air	V	alv	es	3	
				2" CLASS 125 DEEP							
	REDRAWN:	DATE:	١	VELL	AIF	RELE	ASE	V	AL۱	۷E	
	CHECKED: BJL	9-10-03	SIZE			DWG NO.				Т	REV
APPROVED	DRAWN:	5 00	C			DL21					U
	DJF	9-10-03	SCALE	0.75 = 1.00	ASSEMBLY	DRAWING	SHEET	1	OF	1	