



DEEP WELL AIR RELEASE VALVE PARTS LIST				
PART NO.	DWG. NO.	DESCRIPTION	MATERIAL	QTY.
1D	10-1D	DEEP WELL TOP	CAST IRON	1
1DS	10-1DS	DEEP WELL STEM	STEEL	1
1DN	60-12	NUT	STEEL	1
2	3-2C	FLANGE	CAST IRON	1
3	3-3C	BODY	CAST IRON	1
4	3-4	GASKET	ARMSTRONG	1
5	3-5	SEAT	BUNA-N RUBBER	1
6S	3-6S	FLOAT	STAINLESS STEEL	1
11	3-11	BOLT	STEEL	6
12	3-12	NUT	STEEL	6
29A	PLG-.5	PLUG	BRASS	1
29B	.25SOCHDNPTPL	PLUG	BRASS	1
DEEP WELL AIR RELEASE VALVE PARTS LIST				
CP1	NPL 2X3	NIPPLE	STEEL	1
CP2	202-9FH	COMP. FLANGE	CAST IRON	1

INLET FLANGE DATA	
FLANGE DIAMETER	6.50 in.
FLANGE THICKNESS	0.88 in.
BOLT CIRCLE DIAMETER	5.00 in.
NUMBER OF BOLT HOLES	8
BOLT HOLE DIAMETER	0.75 in.

NOTES:

1. INLET SIZE: 2" CLASS 250 FLANGED
OUTLET SIZE: 2" NPT.
2. APPROXIMATE WEIGHT - 58 lbs.
3. WHEN OPERATING PRESSURE IS BELOW 20 psig, REPLACE ITEM NO. 5 WITH SOFT SEATING MATERIAL DWG. NO. 3-5-L.
4. WHEN OPERATING PRESSURE IS ABOVE 150 psig, REPLACE ITEM NO. 5 WITH HARD SEATING MATERIAL DWG. NO. 3-5-H.

DO NOT SCALE DRAWING		<h2 style="margin: 0;">Crispin Valves</h2> <h3 style="margin: 0;">2" CLASS 250 DEEP WELL AIR RELEASE VALVE</h3>		
DIMENSIONS ARE IN INCHES				
REDRAWN:	DATE:	SIZE C	DWG. NO. DL22	REV 0
CHECKED: DJF	2-22-07			
DRAWN: DJF	2-22-07			
SCALE 0.75 = 1.00		ASSEMBLY DRAWING		SHEET 1 OF 1

REV	DESCRIPTION	DATE	APPROVED
REVISIONS			