



PARTS LIST				
PART NO.	DWG. NO.	DESCRIPTION	MATERIAL	QTY.
1D	12-1D	DEEP WELL TOP	CAST IRON	1
1DS	12-1DS	DEEP WELL STEM	STEEL	1
1DN	60-12	NUT	STEEL	1
2	5-2C	FLANGE	CAST IRON	1
3	5-3C	BODY	CAST IRON	1
4	5-4	GASKET	ARMSTRONG	1
5	5-5	SEAT	BUNA-N-RUBBER	1
6	5-6S	FLOAT	STAINLESS STEEL	1
11	30-33	BOLT	STEEL	8
12	4-12	NUT	STEEL	6
29A	PLG-.5	PLUG	BRASS	1
29B	.25SOCHDNPTPL	PLUG	BRASS	1
55	EN 5/8" -11	EYENUT	STEEL	2

NOTES:

1. INLET SIZE: 4" NPT.
OUTLET SIZE: 4" NPT.
2. APPROXIMATE WEIGHT - 187 lbs.
3. WHEN OPERATING PRESSURE IS BELOW 20 psig, REPLACE ITEM NO. 5 WITH SOFT SEATING MATERIAL DWG. NO. 5-5-L.
4. WHEN OPERATING PRESSURE IS ABOVE 150 psig, REPLACE ITEM NO. 5 WITH HARD SEATING MATERIAL DWG. NO. 5-5-H.

<small>DO NOT SCALE DRAWING DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED LINEAR TOLERANCE: ± 0.015</small>		<h2 style="margin: 0;">Crispin Air Valves</h2> <h3 style="margin: 0;">4" DEEP WELL AIR AND VACUUM VALVE</h3>		
REDRAWN:	DATE:	SIZE:	DWG. NO.:	REV:
CHECKED: BJL	7-9-13	C	DL40	0
DRAWN: DJF	7-9-13	SCALE 0.50 = 1.00	SHEET 1	OF 1

REV	DESCRIPTION	DATE	APPROVED
REVISIONS			