



PARTS LIST				
ITEM NO.	PART NUMBER	DESCRIPTION	MATERIAL	QTY.
1	1212-1F	BODY	DUCTILE IRON	1
2	1212-2R	RESILIENT SEAT RING	BUNA-N & AL-BRZ	1
3	1212-3	DISC	AL-BRONZE	1
4	1212-4	SPRING	STAINLESS STEEL	1
5	1212-5	BUSHING	AL-BRONZE	1
6	BHCS.25X.500	SCREW	STAINLESS STEEL	2
7	1010-8	RETAINING RING	STAINLESS STEEL	1
8	1212-30	SHAFT	AL-BRONZE	1

FLANGE DATA	
FLANGE DIAMETER	19.00 in.
FLANGE THICKNESS	1.25 in.
BOLT CIRCLE DIAMETER	17.00 in.
NUMBER OF BOLT HOLES	12
BOLT HOLE DIAMETER	1.00 in.

- NOTES:**
- INLET SIZE: 12" CL. 150 FLANGED  
OUTLET SIZE: 12" CL. 150 FLANGED
  - APPROXIMATE WEIGHT: 308 lbs
  - VALVE WILL BE COATED EXTERNALLY WITH PHENOLIC ALKYD PRIMER

REV.	DESCRIPTION	DATE	APPROVED
1	REDRAWN IN SOLIDWORKS	9-22-21	BJL

UNLESS OTHERWISE SPECIFIED:		
DIMENSIONS ARE IN INCHES	NAME	DATE
XX DIMENSIONS ±.1	DRAWN	DJF 9-22-21
XXX DIMENSIONS ±.01	CHECKED	- -
XXXX DIMENSIONS ±.005	ENG APPR.	- -
DRILLED HOLES ±.01	MFG APPR.	- -
ANGLES ±.1°	Q.A.	- -
CONCENTRIC DIAMETERS SEE BELOW	FILE LOCATION:	\\S2\sl1\Drawings\ASSEMBLY\GC\
MACHINED TO CAST .005 TIR	MATERIAL:	PER BOM
MACHINED SURFACES .125 BMS	FINISH:	
REMOVE CHAMFERS	FILE NAME:	GC121.R 8280585 r1
BREAK SHARP EDGES		

REVISIONS		
<b>CRISPIN VALVES</b>		
TITLE:		
12" CL. 150 RESILIENT SEAT GLOBE CHECK VALVE		
SIZE	DWG. NO.	REV
<b>B</b>	GC121.R 8280585	1
SCALE: 0.38:1	WT: LB	SHEET 1 OF 1

PROPRIETARY AND CONFIDENTIAL  
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF CRISPIN VALVE. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF CRISPIN VALVE IS PROHIBITED.

DO NOT SCALE DRAWING