



PARTS LIST				
ITEM NO.	PART NUMBER	DESCRIPTION	MATERIAL	QTY.
1	1212-1FH	BODY	DUCTILE IRON	1
2	1212-2	SEAT RING	AL-BRONZE	1
3	1212-3	DISC	AL-BRONZE	1
4	1212-4	SPRING	STAINLESS STEEL	1
5	1212-5	BUSHING	AL-BRONZE	1
6	BHCS.25X.50	SCREW	STAINLESS STEEL	2
7	1010-8	RETAINING RING	STAINLESS STEEL	1
8	1212-30	SHAFT	AL-BRONZE	1

FLANGE DATA	
FLANGE DIAMETER	20.50 in.
FLANGE THICKNESS	2.00 in.
BOLT CIRCLE DIAMETER	17.75 in.
NUMBER OF BOLT HOLES	16
BOLT HOLE DIAMETER	1.25 in.

- NOTES:**
- INLET SIZE: 12" CL. 300 FLANGED  
OUTLET SIZE: 12" CL. 300 FLANGED
  - APPROXIMATE WEIGHT: 389 lbs
  - VALVE WILL BE COATED EXTERNALLY WITH PHENOLIC ALKYD PRIMER

REV.	DESCRIPTION	DATE	APPROVED
1	REDRAWN IN SOLIDWORKS	10-5-21	BJL

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
1	REDRAWN IN SOLIDWORKS	10-5-21	BJL

**CRISPIN VALVES**

TITLE:  
12" CL. 300 GLOBE CHECK VALVE

FILE LOCATION:  
\\S2\sl1\Drawings\ASSEMBLY\GC\

FILE NAME: GC123 8280609 r1

SCALE: 0.38:1 WT: LB SHEET 1 OF 1

UNLESS OTHERWISE SPECIFIED:	NAME	DATE
DIMENSIONS ARE IN INCHES	DRAWN	DJF
XXX DIMENSIONS ±.1	CHECKED	-
XXXX DIMENSIONS ±.05	ENG APPR.	-
DRILLED HOLES ±.01	MFG APPR.	-
ANGLES ±.1°	Q.A.	-
CONCENTRIC DIAMETERS SEE BELOW		
MACHINED TO CAST .005 TIR		
MACHINED SURFACES .125 BMS		
REMOVE CHAMFERS		
BREAK SHARP EDGES		

PROPRIETARY AND CONFIDENTIAL  
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF CRISPIN VALVE. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF CRISPIN VALVE IS PROHIBITED.

DO NOT SCALE DRAWING

MATERIAL:  
PER BOM

FINISH: