



PARTS LIST				
ITEM NO.	PART NUMBER	DESCRIPTION	MATERIAL	QTY.
1	2020-1FH	BODY	DUCTILE IRON	1
2	2020-2R	RESILIENT SEAT RING	BUNA-N & AL-BRZ	1
3	2020-3	DISC	AL-BRONZE	1
4	2020-4	SPRING	STAINLESS STEEL	1
5	2020-5	BUSHING	AL-BRONZE	1
6	SHCS.25X.75	SCREW	STAINLESS STEEL	8
7	2020-8	RETAINING RING	STAINLESS STEEL	1
8	2020-30A	DISC SHAFT	AL-BRONZE	1
9	2020-30B	SEAT SHAFT	STAINLESS STEEL	1
10	FHN1.25-7	SHAFT NUT	STAINLESS STEEL	1

FLANGE DATA	
FLANGE DIAMETER	30.50 in.
FLANGE THICKNESS	2.50 in.
BOLT CIRCLE DIAMETER	27.00 in.
NUMBER OF BOLT HOLES	24
BOLT HOLE DIAMETER	1.38 in.

- NOTES:**
- INLET SIZE: 20" CL. 300 FLANGED
OUTLET SIZE: 20" CL. 300 FLANGED
 - APPROXIMATE WEIGHT: 1061 lbs
 - VALVE WILL BE COATED EXTERNALLY WITH PHENOLIC ALKYD PRIMER

REV.	DESCRIPTION	DATE	APPROVED
1	REDRAWN IN SOLIDWORKS	10-12-21	BJL

REVISIONS			TITLE:
NO.	NAME	DATE	
1	DJF	10-12-21	CRISPIN VALVES 20" CL. 300 RESILIENT SEAT GLOBE CHECK VALVE
2	-	-	
3	-	-	
4	-	-	
5	-	-	

UNLESS OTHERWISE SPECIFIED:	
DIMENSIONS ARE IN INCHES	
XX DIMENSIONS	+ .1
XXX DIMENSIONS	+ .01
XXXX DIMENSIONS	+ .005
DRILLED HOLES	+ .01
ANGLES	+ .1°
CONCENTRIC DIAMETERS	SEE BELOW
MACHINED	005 TIR
MACHINED TO CAST	02 TIR
MACHINED SURFACES	125 BMS
REMOVE CHAMFERS	
BREAK SHARP EDGES	
MATERIAL:	FILE LOCATION: \\S2\sl1\Drawings\ASSEMBLY\GC\
FINISH:	FILE NAME: GC203.R 8280809 r1

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF CRISPIN VALVE. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF CRISPIN VALVE IS PROHIBITED.

DO NOT SCALE DRAWING

SIZE	DWG. NO.	REV
B	GC203.R 8280809	1
SCALE: 0.25:1	WT: LB	SHEET 1 OF 1