



PARTS LIST				
ITEM NO.	PART NUMBER	DESCRIPTION	MATERIAL	QTY.
1	303-1FH	BODY	DUCTILE IRON	1
2	303-2	SEAT RING	AL-BRONZE	1
3	303-3	DISC	AL-BRONZE	1
4	303-4	SPRING	STAINLESS STEEL	1
5	303-5	BUSHING	AL-BRONZE	1
6	BHCS.25X.50	SCREW	STAINLESS STEEL	2
7	68-11A	RETAINING RING	STAINLESS STEEL	1

FLANGE DATA	
FLANGE DIAMETER	8.25 in.
FLANGE THICKNESS	1.12 in.
BOLT CIRCLE DIAMETER	6.62 in.
NUMBER OF BOLT HOLES	8
BOLT HOLE DIAMETER	0.88 in.

- NOTES:**
- INLET SIZE: 3" CL. 300 FLANGED
OUTLET SIZE: 3" CL. 300 FLANGED
 - APPROXIMATE WEIGHT: 32 lbs
 - VALVE WILL BE COATED EXTERNALLY WITH PHENOLIC ALKYD PRIMER

REV.	DESCRIPTION	DATE	APPROVED
1	REDRAWN IN SOLIDWORKS	10-5-21	BJL

REVISIONS			TITLE:
REV.	DESCRIPTION	DATE	
1	REDRAWN IN SOLIDWORKS	10-5-21	CRISPIN VALVES
1	3" CL. 300 GLOBE CHECK VALVE		
SIZE	DWG. NO.	REV	
B	GC33 8280289	1	
SCALE: 1:1	WT: LB	SHEET 1 OF 1	

UNLESS OTHERWISE SPECIFIED:		
DIMENSIONS ARE IN INCHES	NAME	DATE
XX DIMENSIONS ±.1	DRAWN	DJF 10-5-21
XXX DIMENSIONS ±.01	CHECKED	- -
XXXX DIMENSIONS ±.005	ENG APPR.	- -
DRILLED HOLES ±.01	MFG APPR.	- -
ANGLES ±.1	Q.A.	- -
CONCENTRIC DIAMETERS SEE BELOW	FILE LOCATION:	
MACHINED TO CAST .005 TIR	\\S2\sl1\Drawings\ASSEMBLY\GC\	
MACHINED SURFACES 125 BMS	FILE NAME: GC33 8280289 r1	
REMOVE CHAMFERS		
BREAK SHARP EDGES		
MATERIAL:	PER BOM	
FINISH:		

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF CRISPIN VALVE. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF CRISPIN VALVE IS PROHIBITED.

DO NOT SCALE DRAWING