



PARTS LIST				
ITEM NO.	PART NUMBER	DESCRIPTION	MATERIAL	QTY.
1	303-1FH	BODY	DUCTILE IRON	1
2	303-2R	RESILIENT SEAT RING	BUNA-N & AL-BRZ	1
3	303-3	DISC	AL-BRONZE	1
4	303-4	SPRING	STAINLESS STEEL	1
5	303-5	BUSHING	AL-BRONZE	1
6	BHCS.25X.50	SCREW	STAINLESS STEEL	2
7	68-11A	RETAINING RING	STAINLESS STEEL	1

FLANGE DATA	
FLANGE DIAMETER	8.25 in.
FLANGE THICKNESS	1.12 in.
BOLT CIRCLE DIAMETER	6.62 in.
NUMBER OF BOLT HOLES	8
BOLT HOLE DIAMETER	0.88 in.

- NOTES:**
- INLET SIZE: 3" CL. 300 FLANGED  
OUTLET SIZE: 3" CL. 300 FLANGED
  - APPROXIMATE WEIGHT: 32 lbs
  - VALVE WILL BE COATED EXTERNALLY WITH PHENOLIC ALKYD PRIMER

REV.	DESCRIPTION	DATE	APPROVED
1	REDRAWN IN SOLIDWORKS	10-5-21	BJL

REVISIONS				
NAME	DATE	<p align="center"><b>CRISPIN VALVES</b></p> <p>TITLE:</p> <p align="center"><b>3" CL. 300 RESILIENT SEAT GLOBE CHECK VALVE</b></p>		
DRAWN	DJF			10-5-21
CHECKED	-			-
ENG APPR.	-			-
MFG APPR.	-			-
Q.A.	-	-	-	
FILE LOCATION:		\\S2\sl1\Drawings\ASSEMBLY\GC\		
FILE NAME:		GC33.R 8280297.r1		
SIZE	DWG. NO.	REV		
<b>B</b>	GC33.R 8280297	1		
SCALE: 1:1	WT: LB	SHEET 1 OF 1		

UNLESS OTHERWISE SPECIFIED:	
DIMENSIONS ARE IN INCHES	
XX DIMENSIONS	+0.1
XXX DIMENSIONS	+0.01
XXXX DIMENSIONS	+0.005
DRILLED HOLES	+0.01
ANGLES	+1°
CONCENTRIC DIAMETERS	SEE BELOW
MACHINED	005 TIR
MACHINED TO CAST	02 TIR
MACHINED SURFACES	125 BMS
REMOVE CHAMFERS	
BREAK SHARP EDGES	
MATERIAL:	PER BOM
FINISH:	

**PROPRIETARY AND CONFIDENTIAL**  
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF CRISPIN VALVE. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF CRISPIN VALVE IS PROHIBITED.

DO NOT SCALE DRAWING