



PARTS LIST				
ITEM NO.	PART NUMBER	DESCRIPTION	MATERIAL	QTY.
1	808-1FH	BODY	DUCTILE IRON	1
2	808-2R	RESILIENT SEAT RING	BUNA-N & AL-BRZ	1
3	808-3	DISC	AL-BRONZE	1
4	808-4	SPRING	STAINLESS STEEL	1
5	808-5	BUSHING	AL-BRONZE	1
6	BHCS.25X.500	SCREW	STAINLESS STEEL	2
7	808-8	EXT RETAINING RING	STAINLESS STEEL	1
8	808-30	SHAFT	AL-BRONZE	1

FLANGE DATA	
FLANGE DIAMETER	15.00 in.
FLANGE THICKNESS	1.62 in.
BOLT CIRCLE DIAMETER	13.00 in.
NUMBER OF BOLT HOLES	12
BOLT HOLE DIAMETER	1.00 in.

**NOTES:**

- INLET SIZE: 8" CL. 300 FLANGED  
OUTLET SIZE: 8" CL. 300 FLANGED
- APPROXIMATE WEIGHT: 174 lbs
- VALVE WILL BE COATED EXTERNALLY WITH PHENOLIC ALKYD PRIMER

REV.	DESCRIPTION	DATE	APPROVED
1	REDRAWN IN SOLIDWORKS	9-22-21	BJL

UNLESS OTHERWISE SPECIFIED:		
DIMENSIONS ARE IN INCHES		
XX DIMENSIONS	±.1	
XXX DIMENSIONS	±.01	
XXXX DIMENSIONS	±.005	
DRILLED HOLES	±.01	
ANGLES	±.1°	
CONCENTRIC DIAMETERS	SEE BELOW	
MACHINED	005 TIR	
MACHINED TO CAST	02 TIR	
MACHINED SURFACES	125 BMS	
REMOVE CHAMFERS		
BREAK SHARP EDGES		
MATERIAL:	PER BOM	FILE LOCATION: \\S2\sl1\Drawings\ASSEMBLY\GC\
FINISH:		FILE NAME: GC83.R 8280489 r1

REVISIONS		
NAME	DATE	
DRAWN	DJF	10-5-21
CHECKED	-	-
ENG APPR.	-	-
MFG APPR.	-	-
Q.A.	-	-
<b>CRISPIN VALVES</b>		
TITLE:		
8" CL. 300 RESILIENT SEAT GLOBE CHECK VALVE		
SIZE	DWG. NO.	REV
<b>B</b>	GC83.R 8280489	1
SCALE: 0.5:1	WT: LB	SHEET 1 OF 1

PROPRIETARY AND CONFIDENTIAL  
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF CRISPIN VALVE. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF CRISPIN VALVE IS PROHIBITED.

DO NOT SCALE DRAWING