



PARTS LIST				
PART NO.	DWG. NO.	DESCRIPTION	MATERIAL	QTY.
1	13-1N	SEAT	PVC	1
2	13-4N	VALVE PLUNGER	BUNA-N & S/S	1
3	13-3N	NUT	STAINLESS STEEL	1
3W	13-3W	LOCKWASHER	STAINLESS STEEL	1
5	13-5R	VALVE FULCRUM	STAINLESS STEEL	1
6	26-6S	VALVE LEVER	STAINLESS STEEL	1
7	13-7R	LINK	STAINLESS STEEL	2
8	13-8R	BALL FULCRUM	STAINLESS STEEL	1
9	36-9	FLOAT	STAINLESS STEEL	1
10	13-10R	BALL LEVER	STAINLESS STEEL	1
11	13-11R	BEARING PIN	STAINLESS STEEL	2
12	13-12R	BEARING PIN	STAINLESS STEEL	1
13	13-11AR	BEARING PIN	STAINLESS STEEL	2
14	2-12	NUT	STEEL	2
15	18-7A	COTTER PIN	STAINLESS STEEL	5
17	3-11	BOLT	STEEL	7
18	3-12	NUT	STEEL	7
19	1-1S	TOP	CAST IRON	1
20	36-2	FLANGE	CAST IRON	1
21	36-21-2L	BODY, 2" NPT	CAST IRON	1
22	13-22	FULCRUM WASHER	FIBRE	2
22A	13-26	FULCRUM WASHER	FIBRE	1
23	13-23	SEAT GASKET	BUNA-N RUBBER	1
24	14-24	FLANGE GASKET	ARMSTRONG	1
25	13-25	BOLT	STAINLESS STEEL	1
30	36-30A	FLOAT ROD	STAINLESS STEEL	1
40	36-33	1" PLUG	CAST IRON	2

ORIFICE DATA	
DIAMETER	MAX. WORKING PRESSURE
1/2	150 PSIG
7/16	200 PSIG
3/8	250 PSIG
1/4	300 PSIG

NOTES:

1. INLET SIZE: 2" NPT; OUTLET SIZE: 1/2" NPT.
2. APPROXIMATE WEIGHT - 93 lbs.
3. FOR OPERATING PRESSURE BELOW 20 psig, REPLACE ITEM No. 2 WITH PART No. 15-4N SOFT SEATING MATERIAL.
4. FOR OPERATING PRESSURE ABOVE 150 psig, REPLACE ITEM No. 2 WITH PART No. 28-4N HARD SEATING MATERIAL.

DO NOT SCALE DRAWING DIMENSIONS ARE IN INCHES		Crispin Air Valves		
		2" NPT. PRESSURE AIR RELEASE SEWER VALVE		
REDRAWN:	DATE:	SIZE:	DWG. NO.:	REV.:
CHECKED: B.J.L.	3-28-12	C	S20	0
DRAWN: DJF	3-28-12	SCALE 1/2" = 1"	ASSEMBLY PRINT	SHEET 1 OF 1

REV	DESCRIPTION	DATE	APPROVED
REVISIONS			