



SEWER AIR / VACUUM RELEASE VALVE PARTS LIST				
ITEM NO.	PART NUMBER	DESCRIPTION	MATERIAL	QTY.
1	36-A6X-2	COVER FLANGE	CAST IRON	1
2	36-A6-3FH	BODY	CAST IRON	1
3	60-4	COVER GASKET	ARMSTRONG	1
4	36-A6X-5	SEAT	BUNA-N RUBBER	1
5	36-A6X-3	SEAT RETAINER	STAINLESS STEEL	1
6	36-A6-6	VALVE	STAINLESS STEEL	1
7	36-A6X-7	ROD GUIDE STAND	STAINLESS STEEL	1
8	36-A6-8	FLOAT ROD GUIDE	NYLATRON	1
9	JFHN.1.125-7	FLOAT GUIDE NUT	STAINLESS STEEL	1
10	36-A6-9	FLOAT	STAINLESS STEEL	1
11	36-A6X-13	STAND OFF	STAINLESS STEEL	4
12	HHCS.375X.88	SEAT RETAINER BOLT	STAINLESS STEEL	8
13	HHCS.625X3.0	COVER BOLT	STEEL	8
14	FHN.625-11	COVER NUT	STEEL	8
BACK FLUSHING PARTS LIST				
16	HA 1X5	HOSE	CAD. PLT STL, RUBBER	1
17	NPL 1XC	NIPPLE	STEEL	2
18	BV-1	BALL VALVE	BRONZE	2

FLANGE DATA	
FLANGE DIAMETER	12.50 in.
FLANGE THICKNESS	1.44 in.
BOLT CIRCLE DIAMETER	10.62 in.
NUMBER OF BOLT HOLES	12
BOLT HOLE DIAMETER	0.88 in.

- NOTES:  
 1. INLET SIZE: 6" CL. 250 FLANGE  
 OUTLET SIZE: 6" NPT  
 2. APPROXIMATE WEIGHT: 216 lbs  
 3. VALVE WILL BE COATED EXTERNALLY WITH PHENOLIC ALKYD PRIMER

REV.	DESCRIPTION	DATE	APPROVED
1	REDRAWN IN SOLIDWORKS	1-18-22	

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES		NAME	DATE
XXX DIMENSIONS	1/16	DJF	1-18-22
XXX DIMENSIONS	1/32	CHECKED	-
XXX DIMENSIONS	1/64	ENG APPR.	-
XXX DIMENSIONS	1/128	MFG APPR.	-
XXX DIMENSIONS	1/256	QA:	-
XXX DIMENSIONS	1/512	FILE LOCATION:	
XXX DIMENSIONS	1/1024	FILE NAME:	S62AB-X_8278624.r1
XXX DIMENSIONS	1/2048	FINISH:	-
XXX DIMENSIONS	1/4096		

PROPRIETARY AND CONFIDENTIAL  
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF CRISPIN VALVES. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF CRISPIN VALVES IS PROHIBITED.  
 DO NOT SCALE DRAWING

**CRISPIN VALVES**

TITLE:  
 6" CL. 250, HIGH CAPACITY SEWER AIR / VACUUM RELEASE VALVE W/ BACK FLUSH

SIZE	DWG. NO.	REV
C	S62AB 8278624	1

SCALE: 0.5:1 WT: LB SHEET 1 OF 1